June 2009

# MONTHLY OPERATIONAL REPORT - Data Sheet
## SLOW SAND, DIATOMACEOUS EARTH & OTHER FILTRATION

Required Number of Turbidity Readings Per Day: [ 1 ]

PWSID #: _C-0207504_

| DAY | TURBIDITY (NTU) ☐ Continuous Sampling ☒ Grab Sampling 12 to 4 | 4 to 8 | 8 to 12 | 12 to 4 | 4 to 8 | 8 to 12 | HIGHEST TURBIDITY READING | TIME TURBIDITY READ | RESIDUAL DISINFECTANT (mg/L) ☐ Continuous Sampling ☒ Grab Sampling ENTRY POINT TO DISTRIBUTION 12 to 4 | 4 to 8 | 8 to 2 | 12 to 4 | 4 to 8 | 8 to 12 | LOWEST RESIDUAL READING | 12. COMMENTS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | | | | | .35 | | .35 | 5:15P | | | | 1.0 | | | 1.0 | |
| 2 | | .34 | | | | | .34 | 8:15A | | | .5 | | | | .5 | |
| 3 | | .29 | | | | | .29 | 11:30A | | | .7 | | | | .7 | |
| 4 | | .37 | | | | | .37 | 10:45A | | | .7 | | | | .7 | |
| 5 | | .32 | | | | | 32 | 9:15P | | | .8 | | | | .8 | |
| 6 | | .36 | | | | | 36 | 10:15A | | | .8 | | | | .8 | |
| 7 | | | | | .40 | | .40 | 6:20P | | | | .7 | | | .7 | |
| 8 | .32 | | | | | | .32 | 7:05A | .8 | | | | | | .8 | |
| 9 | | | | .36 | | | .36 | 1:30P | | | | .8 | | | .8 | |
| 10 | | | | .32 | | | .32 | 2:00P | | | | .8 | | | .8 | |
| 11 | | | | | .23 | | .23 | 4:30P | | | | .5 | | | .5 | |
| 12 | | .25 | | | | | .25 | 11:00A | | | .6 | | | | .6 | |
| 13 | | | | .35 | | | .35 | 3:00P | | | | 1.2 | | | 1.2 | |
| 14 | | | | | .21 | | .21 | 7:00P | | | | | 0.9 | | 0.9 | |
| 15 | | | | | .26 | | .26 | 5:20P | | | | | .8 | | .8 | |
| 16 | | | | .28 | | | .28 | 3:00P | | | .8 | | | | .8 | |
| 17 | | | .26 | | | | .26 | 9:30A | | | .8 | | | | .8 | |
| 18 | | | | .23 | | | .23 | 3:15P | | | | 1.2 | | | 1.2 | |
| 19 | | | .18 | | | | .18 | 11:00A | | | 1.1 | | | | 1.1 | |
| 20 | | | | | .24 | | .24 | 6:45P | | | | 1.0 | | | 1.0 | |
| 21 | | | .26 | | | | .26 | 10:40A | | | 1.0 | | | | 1.0 | |
| 22 | | | | | .26 | | .26 | 4:30P | | | | .7 | | | .7 | |
| 23 | | | .28 | | | | .28 | 9:30A | | | .8 | | | | .8 | |
| 24 | | | .28 | | | | .28 | 8:05A | | | .8 | | | | .8 | |
| 25 | | | .42 | | | | .42 | 11:00A | | | .7 | | | | .7 | |
| 26 | | | .38 | | | | .38 | 9:15A | | | .7 | | | | .7 | |
| 27 | | | | .26 | | | .26 | 3:00P | | | | 1.1 | | | 1.1 | |
| 28 | | .24 | | | | | .24 | 10:30A | | | 1.3 | | 1 | | 1.3 | |
| 29 | | | | | .24 | | .24 | 5:00 | | | | | 1.1 | | 1.1 | |
| 30 | | | | | .33 | | .33 | 4:30P | | | | | 1.2 | | 1.2 | |
| 31 | | | | | | | | | | | | | | | | |

***If at **Any Time** the combined filter effluent turbidity exceeds 5 NTU (>5.49), the state must be notified as soon as possible, but <u>not later than the end of the next business day</u>.***

ESWTR Form 1_Version 3hc_Other

2

January 25, 2005